

U.S. PATENT APPLICATION

Inventor(s): Kazunori SUZUKI
Tooru MATSUMOTO
Kenichiro TAKADA

Invention: HOLOGRAM SCREEN

***NIXON & VANDERHYE P.C.
ATTORNEYS AT LAW
1100 NORTH GLEBE ROAD
8TH FLOOR
ARLINGTON, VIRGINIA 22201-4714
(703) 816-4000
Facsimile (703) 816-4100***

SPECIFICATION

HOLOGRAM SCREEN

BACKGROUND OF THE INVENTION

5 1. Field of the Invention

The present invention relates to a hologram screen that is capable of regenerating an image by diffracting projected light.

10 2. Description of Related Art

A hologram screen that is capable of regenerating an image by diffracting projected light has been conventionally utilized, for example, for the purpose of displaying an advertisement on a shop window. As a versatile form of the above-mentioned hologram
15 screen, a screen formed by applying a hologram film to a resin plate with an adhesive has been known.

However, in the above-mentioned conventional hologram screen, the hologram film is exposed at its surface. Therefore, the hologram film may be separated
20 from the resin plate, or may be scratched or otherwise damaged.

The resin plate may also be damaged. The above-mentioned hologram film is applied to the resin plate with an adhesive, and it is difficult to separate
25 the hologram film from the resin plate without damaging the film. Therefore, when the resin plate is damaged, it is not possible to replace the resin plate with a new one to reuse the hologram film. Therefore, once the resin plate is damaged, the expensive hologram film has to be
30 discarded. Further, when the hologram screen is leased, it is not possible to extend the rental use for a long period due to the above-mentioned problem.

SUMMARY OF THE INVENTION

It is an object of the present invention to overcome
35 the aforementioned problem associated with the previous hologram screen and to provide a hologram screen which is capable of preventing separation and damage of the

hologram film, and permits the hologram film to be reused easily, and which can be rented satisfactorily for a long period.

According to a first aspect of the invention, a
5 hologram screen is provided which comprises a hologram film having the function of diffracting the light projected from a projector, and a first and a second transparent members which sandwich the hologram film so as to cover the film both from a front surface and from a
10 back surface, characterized in that at least one of the first and the second transparent members is replaceable.

The most remarkable feature of the present invention is that the first and second transparent members sandwich the hologram film so as to cover same both from a front
15 surface and from a back surface.

Terms, "front surface" and "back surface", are used herein only for convenience. As used herein, "front surface" means the surface on the side on which the first transparent member is located and "back surface" means
20 the surface on the side on which the above-mentioned second transparent member is located.

Next, the operative effect of the present invention will be described.

In the above-mentioned hologram screen, the first
25 and second transparent members sandwich the hologram film so as to cover same between them.

Therefore, there is no risk of the hologram film separating from the first transparent member or from the second transparent member. Also, the hologram film is
30 protected from being damaged.

Further, even if the first or second transparent member is damaged, the hologram film can be released from the sandwiching by the first and second transparent members and the damaged transparent member may be
35 replaced with a new transparent member to thereby reuse the hologram film.

As described above, in accordance with the present

invention, a hologram screen is provided in which the hologram film can be protected from separation and damage, and can be easily reused.

5 Next, according to a second aspect of the present invention, the first and second transparent members are preferably fixed to each other with screws.

10 The hologram film can be thereby easily and securely sandwiched between the first and second transparent members. Since the first and second transparent members can be easily detached from each other, reuse of the hologram film is further facilitated.

15 Next, according to a third aspect of the present invention, the screws can fix the first and second transparent members to each other by penetrating a through hole provided in one of the first and second transparent members and being threaded into a sprue or threaded hole provided in the other.

20 The hologram film can be thereby easily and securely sandwiched between the first and second transparent members, and the reuse of the hologram film is further facilitated.

25 When above-mentioned sprue (HELI-SERT) is used, there is no risk of damage to the first and second transparent members even if the first and second transparent members are attached and detached frequently.

30 According to a fourth aspect of the present invention, the above-mentioned screws can fix the first and second transparent members to each other by penetrating a through-hole provided in both first and second transparent members and being threaded into a nut.

 In this manner, also in this case, the hologram film can be easily and securely sandwiched between the first and second transparent members, and the reuse of the hologram film is further facilitated.

35 There is no risk of damage to the first and second transparent members even if the first and second transparent members are attached and detached frequently.

Next, according to a fifth aspect of the present invention, the first and second transparent members can be fixed to each other with an adhesive.

5 In this case, a hologram screen having a good appearance and design can be obtained.

Next, according to a sixth aspect of the present invention, the first and second transparent members can be fixed to each other with a clip or clips.

10 In this case, a hologram screen that allows a high operational efficiency in mounting and replacing of the first and second transparent members.

15 Next, according to a seventh aspect of the present invention, the first and second transparent members are preferably formed from a resin, a glass, or a plastic film.

A hologram screen capable of regenerating a high quality images can be thereby obtained cheaply.

20 When the first and second transparent members are formed from a resin, a light weight hologram screen can be obtained.

When the first and second transparent members are formed from a plastic film, a hologram screen that can be applied to a window pane as has been done previously is obtained.

25 The above-mentioned resin may include, for example, polycarbonate, acrylic resin, vinyl chloride resin, and the like.

30 Next, according to an eighth aspect of the present invention, an anti-sticking agent is preferably interposed between the hologram film and at least one of the first and second transparent members.

35 For example, when the front surface of the hologram film and the first transparent member are of such a material property that they are likely to stick to each other, the above-mentioned anti-sticking agent is interposed between the front surface of the hologram film and the first transparent members. When the back surface

of the hologram film and the second transparent member are of such a material property that they are likely to stick to each other, the above-mentioned anti-sticking agent may be interposed between the back surface of the
5 hologram film and the second transparent members.

With such a construction, a gap is created between the hologram film and the first or second transparent member, and sticking of the hologram film to the first or second transparent member can be prevented. Degradation
10 of image quality due to local sticking between the hologram film and the first or second transparent member can be thereby prevented. Also, in the state in which images are not being regenerated, the good design and appearance of the hologram screen can be maintained.

15 Next, according to a ninth aspect of the present invention, the aforementioned hologram film is comprised of a hologram layer that has the function of diffracting the light projected from a projector and a PET layer that has the hologram layer applied on at least one of the
20 surfaces thereof and having a hard coat formed thereon. The above-mentioned anti-sticking agent is preferably interposed between the above-mentioned PET layer and at least one of the first and second transparent members.

With such a construction, the surface of the
25 hologram film having a hard coat formed thereon can be prevented from sticking to the first or second transparent member.

Next, according to a tenth aspect of the present invention, the hologram film can be constructed such that
30 the above-mentioned PET layer is applied to either the front surface or the back surface of the above-mentioned hologram layer, and the other surface of the hologram layer is applied to the first or second transparent member.

35 In this case, the hologram film is preferably applied to the transparent member less likely to be damaged based on the condition of use, and the like. For

example, the hologram screen can be constructed using the side to which the hologram film is not applied as the side more likely to be damaged, for example, as the side facing observers.

5 With such a construction, the first or second transparent member that is disposed on the side more likely to be damaged, can be replaced to reuse the hologram film.

10 Next, according to an eleventh aspect of the present invention, the above-mentioned anti-contact agent is preferably spherical, cylindrical or scale-like in shape.

15 With such a construction, a gap is securely provided between the hologram film and the first or second transparent member, and sticking between them can be reliably prevented.

20 Next, according to a twelfth aspect of the present invention, the above-mentioned anti-sticking agent is preferably formed from inorganic material including, as a principal component, silicon dioxide, borosilicate glass, or aluminum oxide, plastic materials including, as a principal component, divinylbenzene or methyl ester methacrylate, or starch such as grape sugar, cane sugar.

25 With such a construction, sticking between the hologram film and the first or second transparent member can be reliably prevented.

30 Next, according to a thirteenth aspect of the present invention, the above-mentioned anti-sticking agent can be formed in powder form and be applied with a brush to the first transparent member, the second transparent member, or the hologram film.

 With such a construction, the anti-sticking agent can be interposed easily and reliably between the hologram film and the first or second transparent member.

35 Next, according to a fourteenth aspect of the present invention, the anti-sticking agent can be formed in an aqueous suspension and be applied by spray coating to the first transparent member, the second transparent

member, or the hologram film.

Also in this case, the above-mentioned anti-sticking agent can be interposed easily and reliably between the hologram film and the first or second transparent member.

5 Next, according to a fifteenth aspect of the present invention, the above-mentioned anti-sticking agent can be formed in aqueous suspension and be applied by spin coating to the first transparent member, the second transparent member, or the hologram film.

10 Also in this case, the above-mentioned anti-sticking agent can be interposed easily and reliably between the hologram film and the first or second transparent member.

15 Next, according to a sixteenth aspect of the present invention, the above-mentioned anti-sticking agent can be suspended in an alcohol solution and be applied by spin coating to the first transparent member, the second transparent member, or the hologram film.

20 Also in this case, the above-mentioned anti-sticking agent can be interposed easily and reliably between the hologram film and the first or second transparent member.

25 Next, according to a seventeenth aspect of the present invention, sealant material for preventing uneven contact is preferably interposed uniformly both between the hologram film and the first transparent member and between the hologram film and the second transparent member.

30 When the hologram film and the first or second transparent member are of such a material property that the contact is likely to become partial (uneven), the above-mentioned sealant material may be interposed between the hologram film and the first transparent member and between the hologram film and the second transparent member, respectively.

35 With such a construction, there is no gap between the hologram film and the first and second transparent members, respectively, and close contact over the entire surface without uneven contact can be achieved.

Degradation of image quality due to the partial contact between the hologram film and the first or the second transparent member can be thereby prevented. Also, in the state in which images are not being regenerated, the good design and appearance of the hologram screen can be maintained. The sticking force of the sealant material with the first and the second transparent members is preferably such that an operator can manually separate the hologram screen from the transparent member with ease.

Next, according to an eighteenth aspect of the present invention, the above-mentioned sealant material is preferably glycerin, triethanolamine, or alcohols having a high boiling point such as ethylene glycol.

With such a construction, close contact between the hologram film and the first and the second transparent members can be achieved reliably and, when replacing the transparent member, the hologram screen can be easily separated from the transparent member.

Next, according to a nineteenth aspect of the present invention, a release agent may be coated on the entire front and back surfaces of the hologram film, and an adhesive layer may be provided via the release agent. Also, on the front and back surfaces, the first and the second transparent members which are larger than the hologram film are respectively applied with the first and the second transparent members being adhered to each other with an adhesive at the portion outside of the periphery of the hologram film.

By coating the above-mentioned release agent, even if the first and the second transparent members which are larger than the hologram film are adhered with an adhesive, the first and second transparent members are not adhered to the hologram film. Thus, the first and the second transparent members are adhered to each other only at the portion outside of the periphery of the hologram film.

Therefore, when the first or the second transparent member is damaged and needs to be replaced, only by cutting and removing the adhered portion, one can take out the hologram film easily with no damage, and use the hologram again.

As the above-mentioned release agent, silicone, for example, may be employed.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1(a) is a front view showing a hologram screen according to Embodiment 1 of the present invention;

Fig. 1(b) is a side view showing a hologram screen according to Embodiment 1 of the present invention;

Fig. 2 is a view useful for explaining the function of the hologram screen according to Embodiment 1;

Fig. 3 is a view useful for explaining fixing means for fixing the first and second transparent members using a screw according to Embodiment 1;

Fig. 4 is a partial enlarged sectional view showing the hologram screen according to Embodiment 1;

Fig. 5 is a partial enlarged sectional view showing the hologram screen according to Embodiment 2;

Fig. 6 is a partial enlarged sectional view showing the hologram screen according to Embodiment 3;

Fig. 7(a) is a view useful for explaining fixing means using a screw and a sprue according to Embodiment 4;

Fig. 7(b) is a view useful for explaining fixing means using a screw and a nut according to Embodiment 4;

Fig. 8(a) is a front view showing a hologram screen according to Embodiment 5;

Fig. 8(b) is a side view showing a hologram screen according to Embodiment 5;

Fig. 8(c) is a top plan view showing a hologram screen according to Embodiment 5;

Fig. 9(a) is a front view showing a hologram screen according to Embodiment 5;

Fig. 9(b) is a side view showing a hologram screen

according to Embodiment 5;

Fig. 10(a) is a front view showing a hologram screen according to Embodiment 6;

5 Fig. 10(b) is a sectional view taken along the line Xb-Xb of Fig. 10(a);

Fig. 11 is a perspective view showing the first transparent member, the hologram film and the second transparent member according to Embodiment 7;

10 Fig. 12 is a rear view showing the hologram screen according to Embodiment 7;

Fig. 13 is a front view showing the hologram screen according to Embodiment 8;

15 Fig. 14 is a sectional view showing the hologram screen applied to a window pane according to Embodiment 8;

Fig. 15 is a view useful for explaining the fabrication method of a hologram screen according to Embodiment 9;

20 Fig. 16 is a view, continued from Fig. 15, that is useful for explaining the fabrication method of a hologram screen according to Embodiment 9;

Fig. 17 is a view continued from Fig. 16 that is useful for explaining the fabrication method of a hologram screen according to Embodiment 9; and

25 Fig. 18 is a view continued from Fig. 17 that is useful for explaining the fabrication method of a hologram screen according to Embodiment 9.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiment 1

30 A hologram screen according to an Embodiment of the present invention will be described below with reference to Figs. 1 through 4.

35 The hologram screen 1 according to the present Embodiment is, as shown in Figs. 1(a) and 1(b), comprised of a hologram film 2 and a first transparent member 31 and a second transparent member 32 which together sandwich the hologram screen 2 so as to cover the same

from a front surface 21 and a back surface 22.

5 The hologram film 2 has the function of diffracting the light 62 projected from a projector 61, as shown in Fig. 2. Thus, the hologram screen 1 is capable of diffracting the light 62 projected from the projector 61 so as to scatter and transmit the light, and thereby causing an observer E to recognize an image. The above-mentioned hologram screen 1 may be of a transmission type as shown, or alternatively, it may be of a reflection
10 type which causes an observer on the side of the projector to recognize an image.

Also, as shown in Fig. 3, the first transparent member 31 and second transparent member 32 are fixed to each other by means of a screw 4. Thus, the above-mentioned screw 4 penetrates a through hole 311 provided
15 in the first transparent member 31, and is threaded into a threaded hole 322 provided in the second transparent member 32, so as to fix the first transparent member 31 and second transparent member 32 to each other.

20 As shown in Fig. 1(a), the above-mentioned screw 4 is disposed at 4 location positioned outside of the hologram film 2.

The first transparent member 31 and the above-mentioned second transparent member 32 are formed from polycarbonate resin.
25

As shown in Fig. 4, an anti-sticking agent 5 is interposed between the hologram film 2 and the first transparent member 31. The anti-sticking agent 5 is spherical in shape, and is made of inorganic material
30 having silicon dioxide as a principal component.

The above-mentioned anti-sticking agent 5 is about 0.5 ~ 100 μm in size, so that a gap 11 approximately 100 μm in length is thereby formed between the aforementioned hologram film 2 and the first transparent member 31.

35 As shown in Fig. 4, the aforementioned hologram film 2 is comprised of a hologram layer 23 and a PET layer 24

applied to the front surface 231 of the hologram layer 23 and having a hard coat 241 formed thereon. The above-mentioned anti-sticking agent 5 is interposed between the above-mentioned PET layer 24 and the first transparent member 31.

A PET layer 25 having no hard coat is applied to the back surface 232 of the above-mentioned hologram layer 23. The above-mentioned PET layers 24, 25 are applied to the hologram film 1 via an adhesive 26.

The method for interposing the above-mentioned anti-sticking agent 5 between the hologram film 2 and the first transparent member 31 may include, for example, the following treatments before sandwiching the hologram film 2 between the first transparent member 31 and second transparent member 32.

Thus, the above-mentioned anti-sticking agent 5 may be prepared in the form of powder, and applied with a brush to the first transparent member 31 or the aforementioned hologram film 2.

Alternatively, the above-mentioned anti-sticking agent 5 may be prepared in the form of aqueous suspension, and applied by spray coating to the first transparent member 31 or the hologram film 2.

Or, the above-mentioned anti-sticking agent 5 may be prepared in the form of aqueous suspension, and applied to the first transparent member 31 or the hologram film 2 by spin coating with a spinner rotating at high speed (500 ~ 1000 rpm).

Or, the above-mentioned anti-sticking agent 5 may be prepared in the form of suspension in alcohol solution, and applied by spin coating to the first transparent member 31 or the hologram film 2.

Next, the operative effect of the present Embodiment will be described below.

In the above-mentioned hologram screen 1, the first transparent member 31 and the second transparent member 32 sandwich the hologram film 2 so as to cover the same.

Therefore, there is no risk that the hologram film 2 is separated from the first transparent member 31 or second transparent member 32. Damage to the hologram film 2 can be thus prevented.

5 Even if the first transparent member 31 or the second transparent member 32 is damaged, sandwiching of the hologram film by the first transparent member 31 and the second transparent member 32 can be released and the damaged transparent member can be replaced with a new
10 transparent member to reuse the hologram film 2.

Since the first transparent member 31 and the second transparent member 32 are fixed to each other by means of screws 4, the first transparent member 31 and second transparent member 32 can easily and securely sandwich
15 the hologram film 2. Also, since the first transparent member 31 and second transparent member 32 can be attached and detached easily, the hologram film 2 can be reused with ease.

Since the first transparent member 31 and second transparent member 32 are formed from a resin, a light-weight hologram screen 1 that can regenerate images of high quality can be obtained cheaply.

The PET layer 24 which is applied on the front surface 21 of the hologram film 2 and which has a hard coat 241 formed thereon, is, in view of material
25 property, likely to stick to the first transparent layer 31 made of a resin. Therefore, an anti-sticking agent 5 is interposed between the hologram film 2 and the first transparent member 31 (Fig. 4).

30 With such a construction, a gap 11 is provided between the hologram film 2 and the first transparent member 31, and sticking of the two surfaces can be thereby prevented. Thus, degradation of the image quality due to the partial sticking of the hologram film
35 2 to the first transparent member 31 can be prevented. Also, while images are not being regenerated, the good design and appearance of the hologram screen can be

maintained.

The PET layer 25 on the back surface 22 of the hologram film 2 has no hard coat formed thereon and is thus unlikely to stick to the aforementioned second transparent member 32. Therefore, even if the above-mentioned anti-sticking agent 5 is not interposed between the hologram film 2 and the aforementioned second transparent member 32, problems such as degradation of image quality of the hologram screen 1 and the like, will not arise.

Since the above-mentioned anti-sticking agent is spherical in shape, a gap 11 can be reliably provided between the hologram film 2 and the first transparent member 31 and sticking of the two surfaces can be reliably prevented.

Also, since the above-mentioned anti-sticking agent is made of inorganic material having silicon dioxide as a principal component, the sticking of the hologram film 2 to the first transparent member 31 can be reliably prevented.

By adopting the method as described above for disposing the anti-sticking agent 5, the anti-sticking agent 5 can be easily and reliably interposed between the hologram film 2 and the first transparent member 31.

As has been described in the foregoing, according to the present Embodiment, a hologram screen that is capable of protecting the hologram film from separation and damage and permitting the hologram film to be reused easily, is provided.

Embodiment 2

The present Embodiment is, as shown in Fig. 5, an example of a hologram screen 10 in which the back surface 22 of the hologram film 20 is adhered to the second transparent member 32.

Thus, the hologram film 20 is the same as the hologram film 2 (Fig. 4) used in the Embodiment 1 except that the PET layer 25 on the back surface 22 is separated

and removed. The hologram film 20 is adhered via an adhesive 26 provided on the back surface 22 to the above-mentioned second transparent member 32.

Otherwise, it is the same as in the Embodiment 1.

5 In this case, the side of the first transparent member 31 to which the hologram film 20 is not adhered can be used as the side on which damage is relatively likely to arise, that is, as the observer's side.

10 With such a construction, even when the first transparent member 31 is damaged, it can be replaced with a new transparent member and the hologram film 20 can be reused.

Otherwise, it has the same operative effect as in the Embodiment 1.

15 Embodiment 3

The present Embodiment is an example of a hologram screen 100 in which, as shown in Fig. 6, an anti-sticking agent 5 is disposed between the hologram film 200 and the first transparent member 31, and between the hologram
20 film 200 and the second transparent member 32.

Otherwise, it is the same as in the Embodiment 1.

With such a construction, even when the back surface 22 of the hologram film 2 is, in terms of material property, likely to stick to the second transparent
25 member 32, the sticking of the two surface can be prevented.

For example, this construction is effective when a hard coat 251 is also formed on the PET layer 25 on the back surface 22 of the hologram film 2.

30 Otherwise, the present Embodiment has the same operative effect as in the Embodiment 1.

Embodiment 4

As shown in Figs. 7(a) and 7(b), the present embodiment is an examples which a sprue 41 (Fig. 7(a)) or
35 a nut 42 (Fig. 7(b)) is used for threading the screw 4 as fixing means for fixing the first transparent member 31 and the second transparent member 32 to each other.

Thus, when the above-mentioned sprue 41 is used, as shown in Fig. 7(a), the screw 4 penetrates a through hole 311 provided in the first transparent member 31, and is threaded into the sprue 41 provided in the second transparent member 32 to thereby fix the first transparent member 31 to the second transparent member 32.

The above-mentioned sprue 41 is embedded so as to be threaded into a threaded hole 323 that is formed beforehand in the above-mentioned second transparent member 32, and the above-mentioned screw 4 is threaded into the sprue 41 embedded in the above-mentioned second transparent member 32.

When the above-mentioned nut 42 is used, as shown in Fig. 7(b), the screw 4 penetrates the through-holes provided both in the first transparent member 31 and second transparent member 32, and is threaded into a nut 42 to thereby fix the first transparent member 31 and second transparent member 32 to each other.

Otherwise, the present Embodiment is the same as Embodiment 1.

With such a construction, the hologram film 2 can be sandwiched easily and reliably between the first transparent member 31 and second transparent member 32, and reuse of the hologram film is thereby further facilitated.

Even if the first transparent member 31 and second transparent member 32 are attached and detached frequently, there is no risk that the first transparent member 31 or second transparent member 32 is damaged.

Otherwise, the present Embodiment has the same operative effect as in the Embodiment 1.

Embodiment 5

As shown in Figs. 8(a) through 8(c) and Figs. 9(a) and 9(b), the present Embodiment is an example of a hologram screen 1a, 1b in which clips 43, 44 are used as fixing means for fixing the first transparent member 31

and second transparent member 32 to each other.

As shown in Figs. 8(a) through 8(c), the above-mentioned hologram screen 1a has clips 43 disposed at two locations on each of opposing end edges 15. Each clip 43 is formed, as shown in Fig. 8(c), in the cross sectional shape Π , and is attached so as to clamp together the first transparent member 31 and second transparent member 32.

The clip 43 is made of, for example, metal or resin, and is biased so as to clamp together the first transparent member 31 and second transparent member 32.

Also, as shown in Figs. 9(a) and 9(b), long clips 44 may be used to clamp together the first transparent member 31 and second transparent member 32 at the two opposing end edges 16 of the hologram screen 1b.

Otherwise, the present Embodiment is the same as the Embodiment 1.

With this construction, a through hole or a threaded hole needs not be formed in the first transparent member 31 or the second transparent member 32, and the hologram screen 1a or 1b can be fabricated easily.

Also, the first transparent member 31 and the second transparent member 32 can be attached and detached easily. When the first transparent member 31 or the second transparent member 32 is damaged, it can be easily replaced with a new one, so that reuse of the hologram film 2 is further facilitated.

As shown in Figs. 9(a) and 9(b), by using the long sized clips 44, the first transparent member 31 and the second transparent member 32 can be fixed to each other more reliably.

Otherwise, the present Embodiment has the same operative effect as in the Embodiment 1.

Embodiment 6

As shown in Figs. 10(a) and 10(b), the present Embodiment is an example of a hologram screen 1c in which the first transparent member 31 and the second

transparent member 32 are fixed to each other with an adhesive 45.

Thus, as shown in Figs. 10(a) and 10(b), an adhesive 45 is interposed between the first transparent member 31 and the second transparent member 32 at the periphery of the hologram film 2, and the first transparent member 31 and second transparent member 32 are adhered to each other with the adhesive 45.

The above-mentioned adhesive 45 is disposed so as not to come into contact with the above-mentioned hologram 2.

Otherwise, the present Embodiment is the same as the Embodiment 1.

In this case, a hologram screen 1c having excellent appearance and design can be obtained.

Otherwise, the present Embodiment has the same operative effect as in the Embodiment 1.

Embodiment 7

As shown in Figs. 11 and 12, the present Embodiment is an example of hologram screen 1d in which a spot facing 37 capable of containing the hologram film 2 is provided as simple means for fixing the hologram film 2 in the first transparent member 31.

Thus, the hologram screen 1d is obtained, as shown in Fig. 11, by placing the hologram film 2 into a spot facing 37 in the first transparent member 31 and covering it from above with the second transparent member 32. As shown in Fig. 12, fitting pins 38 are disposed around the spot facing 37 of the first transparent member 31, and the second transparent member 32 is fixed to the first transparent member 31 with the fitting pins 38.

The spot facing may be provided in the second transparent member 32, instead of the first transparent member 31.

The first transparent member 31 and second transparent member 32 used in the present Embodiment are preferably made of a highly transparent resin such as

acrylic resin or polycarbonate resin.

Also, in order to ensure good design and appearance of the hologram screen 1d, the fitting pins 38 are preferably transparent.

5 Otherwise, the present Embodiment is the same as the Embodiment 1.

10 The hologram screen 1d of the present Embodiment is of the so-called picture frame type. With this construction, the labor of positioning the hologram film can be saved and need for forming a through hole or a threaded hole is eliminated. Therefore, the hologram screen 1d can be fabricated easily. Otherwise, the present Embodiment has the same operative effect as in the Embodiment 1.

15 Embodiment 8

As shown in Figs. 13 and 14, the present Embodiment is an example of a hologram screen 1e in which the same hologram screen 1e as in the Embodiment 6 can be adhered directly to a window pane.

20 As shown in Fig. 13, an adhesive 46 is disposed on the outer surface of the first transparent member 31 or the second transparent member 32 (the second transparent member 32 in Fig. 13).

25 The first transparent member 31 and the second transparent member 32 used herein are PET films.

30 As shown in Figs. 13 and 14, when the first transparent member 31 and the second transparent member 32 are fixed to each other with an adhesive 45, a release agent 47, such as silicone may be applied to the hologram film 2 beforehand, and the above-mentioned adhesive 45 may be applied to the entire surface of the first transparent member 31 or the second transparent member 32.

35 Otherwise, the present Embodiment is the same as the Embodiment 1.

With this treatment, the need to dispose the adhesive 45 only at the periphery of the hologram film 2

as in the Embodiment 6 is eliminated, and the hologram screen can be fabricated easily.

5 The release agent 47 prevents the adhesive 45 from being adhered to the hologram film 2, so that, when the first transparent member 31 or the second transparent member 32 is damaged, by cutting off the portion where the first transparent member 31 and the second transparent member 32 are directly adhered to each other, the hologram film 2 can be taken out and reused easily.

10 Otherwise, the present Embodiment has the same operative effect as in the Embodiment 1.

Embodiment 9

15 As shown in Figs. 15 through 18, the present Embodiment is an example of a hologram screen in which a sealant 61 is used to sandwich the hologram film 2 between the first transparent member 31 and the second transparent member 32.

20 In this case, as shown in Fig. 15, using an injector 62, the above-mentioned sealant 61 is dropped on the first transparent member 31. The amount of dropped sealant 61 is such that the sealant 61 is uniformly spread over the whole surface of the first transparent member 31. When the sealant 61 is sufficiently spread, the hologram film 2 is placed as shown in Figs. 16 and 25 17, and a suitable amount of the sealant 61 is again dropped from above (Fig. 17, Fig. 18). Then, the second transparent member 32 is placed from above so as to sandwich the hologram film 2 between the first transparent member 31 and the second transparent member 32 (Fig. 18). Otherwise, the present Embodiment is the same as the Embodiment 1.

30 With this construction, the hologram film 2 can be brought into close contact with the first transparent member 31 or the second transparent member 32 uniformly over the entire surface. Thus, partial (uneven) contact between the hologram film 2 and the first transparent member 31 or the second transparent member 32 is

35

prevented, and the degradation of image quality can
thereby be prevented. Also, while images are not being
regenerated, the good design and appearance of the
hologram screen can be maintained. Otherwise, the
5 present Embodiment has the same operative effect as in
the Embodiment 1.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226